



**Cogito Group**

DIGITAL IDENTITY AND SECURITY

**X.509 Certificate Policy (CP)**  
**Cogito PKI as a Service - Resource**  
**Certificates**

**27 September 2021**

**Version 1.0**

## X.509 Certificate Policy (CP)

### Notice to all parties seeking to rely

Reliance on a certificate issued under this Certificate Policy, identified by subarcs of the object identifier 1.2.36.151795998.4.1.1.3 is only permitted as set forth in this document. Use of a certificate issued under this CP constitutes acceptance of the terms and conditions set out in this document, as such, acceptance of a certificate by a Relying Party is at the Relying Party's risk. Refer to the CP and Cogito PKIaaS CPS for relevant disclaimers for warranties, liabilities and indemnities.

<b>Owner:</b>	Cogito Governance Risk and Compliance Group
<b>Contact details:</b>	Telephone: +61 2 6140 4494 Email: Security.services@cogitogroup.net
<b>Document status:</b>	RELEASED
© Cogito Group Pty Ltd 2021	
All rights reserved. No part of this publication may be used, copied, reproduced, modified, distributed, displayed, stored in a retrieval system or transmitted in any form by any means (electronic, mechanical, photocopying, recording or otherwise) without the prior written authorisation of Cogito Group Pty Limited. Reproduction and use of all or portions of this publication is not permitted. No rights or permissions are granted with respect to this work.	

Last saved	Filename	Page
27 September 2021	Cogito-PKIaaS-Resource-CP_v1.0.docx	2 of 70

**X.509 Certificate Policy (CP)**

**Document Management**

<b>This document is controlled by:</b>	Cogito Governance Risk and Compliance Group (GRCG)
<b>Changes are authorised by:</b>	Cogito Governance Risk and Compliance Group Gatekeeper Competent Authority (GCA)

<b>Last saved</b>	<b>Filename</b>	<b>Page</b>
27 September 2021	Cogito-PKIaaS-Resource-CP_v1.0.docx	3 of 70

**X.509 Certificate Policy (CP)**

**Revision history**

<b>Revision date</b>	<b>Version No.</b>	<b>Author</b>	<b>Description of changes</b>
2021-09-16	1.0	Brad Fardig	Released

<b>Last saved</b>	<b>Filename</b>	<b>Page</b>
27 September 2021	Cogito-PKIaaS-Resource-CP_v1.0.docx	4 of 70

## Contents

<b>Document Management</b> .....	<b>3</b>
<b>Revision history</b> .....	<b>4</b>
<b>Contents</b> .....	<b>5</b>
<b>1 Introduction</b> .....	<b>12</b>
1.1 Overview .....	12
1.2 Document Name and Identification .....	12
1.3 PKI Participants.....	13
1.3.1 Certification Authorities .....	13
1.3.2 Registration Authorities.....	13
1.3.3 Subscribers .....	13
1.3.4 Relying Parties.....	13
1.3.5 Other Participants .....	13
1.4 Certificate Usage.....	13
1.4.1 Appropriate Certificate Uses.....	13
1.4.2 Prohibited Certificate Uses .....	13
1.5 Policy Administration .....	14
1.5.1 Organisation Administering the Document .....	14
1.5.2 Contact Person .....	14
1.5.3 Authority determining CPS suitability for the policy .....	14
1.5.4 CPS approval procedures.....	14
1.6 Definitions, acronyms and interpretation.....	14
<b>2 Publication and Repository Responsibilities</b> .....	<b>15</b>
2.1 Repositories .....	15
2.2 Publication of certification information .....	15
2.3 Time or Frequency of publication.....	15
2.4 Access controls on repositories .....	15
<b>3 Identification and Authentication</b> .....	<b>16</b>
3.1 Naming.....	16
3.1.1 Types of Names.....	16
3.1.2 Need for Names to be Meaningful .....	16
3.1.3 Anonymity or pseudonymity of Subscribers .....	16
3.1.4 Rules for interpreting various name forms.....	16
3.1.5 Uniqueness of Names .....	16

Last saved	Filename	Page
27 September 2021	Cogito-PKIaaS-Resource-CP_v1.0.docx	5 of 70

## **X.509 Certificate Policy (CP)**

3.1.6	Recognition, authentication, and Role of Trademarks.....	16
3.2	Initial identity validation .....	16
3.2.1	Method to prove possession of private key .....	16
3.2.2	Authentication of organisation entity.....	16
3.2.3	Authentication of individual identity.....	16
3.2.4	Non-Verified Subscriber information.....	17
3.2.5	Validation of authority .....	17
3.2.6	Criteria for interoperation .....	17
3.3	Identification and authentication for re-key requests .....	17
3.3.1	Identification and authentication for routine re-key.....	17
3.3.2	Identification and authentication for re-key after revocation.....	17
3.4	Identification and authentication for revocation requests.....	17
<b>4</b>	<b>Certificate Lifecycle Operational Requirements.....</b>	<b>18</b>
4.1	Certificate Application .....	18
4.1.1	Who can submit a certificate application .....	18
4.1.2	Enrolment process and responsibilities .....	18
4.2	Certificate application processing .....	18
4.2.1	Performing identification and authentication functions .....	18
4.2.2	Approval or rejection of certificate applications .....	18
4.2.3	Time to process certificate applications.....	18
4.3	Certificate Issuance.....	18
4.3.1	CA actions during certificate issuance.....	18
4.3.2	Notification to Subscriber by the CA of issuance of certificate .....	18
4.4	Certificate Acceptance .....	18
4.4.1	Conduct constituting certificate acceptance .....	18
4.4.2	Publication of the certificate by the CA.....	19
4.4.3	Notification of certificate issuance by the CA to other entities.....	19
4.5	Keypair and certificate usage.....	19
4.5.1	Subscriber private key and certificate usage.....	19
4.5.2	Relying Party public key and certificate usage .....	19
4.6	Certificate renewal .....	19
4.6.1	Circumstance for certificate renewal.....	19
4.6.2	Who may request renewal .....	19
4.6.3	Processing certificate renewal requests .....	19

<b>Last saved</b>	<b>Filename</b>	<b>Page</b>
27 September 2021	Cogito-PKIaaS-Resource-CP_v1.0.docx	6 of 70

## X.509 Certificate Policy (CP)

4.6.4	Notification of new certificate issuance to Subscriber .....	19
4.6.5	Conduct constituting acceptance of a renewal certificate.....	20
4.6.6	Publication of the renewal certificate by the CA .....	20
4.6.7	Notification of certificate issuance by the CA to other entities.....	20
4.7	Certificate Re-key.....	20
4.7.1	Circumstance for certificate re-key .....	20
4.7.2	Who may request certification of a new public key.....	20
4.7.3	Processing certificate re-keying requests.....	20
4.7.4	Notification of new certificate issuance to Subscriber .....	20
4.7.5	Conduct constituting acceptance of a re-keyed certificate .....	20
4.7.6	Publication of the re-keyed certificate by the CA.....	20
4.7.7	Notification of certificate issuance by the CA to other entities.....	20
4.8	Certificate modification.....	20
4.8.1	Circumstance for certificate modification .....	20
4.8.2	Who may request certificate modification.....	21
4.8.3	Processing certificate modification requests .....	21
4.8.4	Notification of new certificate issuance to Subscriber .....	21
4.8.5	Conduct constituting acceptance of modified certificate.....	21
4.8.6	Publication of the modified certificate by the CA .....	21
4.8.7	Notification of certificate issuance by the CA to other entities.....	21
4.9	Certificate revocation and suspension .....	21
4.9.1	Circumstances for revocation .....	21
4.9.2	Who can request revocation .....	21
4.9.3	Procedure for revocation request .....	21
4.9.4	Revocation request grace period.....	21
4.9.5	Time within which the CA must process the revocation request.....	22
4.9.6	Revocation checking requirement for relying parties.....	22
4.9.7	CRL issuance frequency (if applicable) .....	22
4.9.8	Maximum latency for CRLs.....	22
4.9.9	Online revocation/status checking availability .....	22
4.9.10	On-line revocation checking requirements.....	22
4.9.11	Other forms of revocation advertisements available.....	22
4.9.12	Special requirements re key compromise.....	22
4.9.13	Circumstances for suspension .....	22

Last saved	Filename	Page
27 September 2021	Cogito-PKIaaS-Resource-CP_v1.0.docx	7 of 70

## **X.509 Certificate Policy (CP)**

4.9.14	Who can request suspension.....	22
4.9.15	Procedure for suspension request.....	22
4.9.16	Limits on suspension period.....	22
4.10	Certificate status services.....	23
4.10.1	Operational Characteristics.....	23
4.10.2	Service Availability.....	23
4.10.3	Optional Features.....	23
4.11	End of subscription.....	23
4.12	Key escrow and recovery.....	23
<b>5</b>	<b>FACILITY, MANAGEMENT, AND OPERATIONAL CONTROLS.....</b>	<b>24</b>
5.1	Physical controls.....	24
5.2	Procedural Controls.....	24
5.3	Personnel controls.....	24
5.4	Audit logging procedures.....	24
5.5	Records archival.....	24
5.5.1	Types of record archived.....	24
5.5.2	Retention period for archive.....	24
5.5.3	Protection of archive.....	24
5.5.4	Archive backup procedures.....	24
5.5.5	Requirements for timestamping of records.....	24
5.5.6	Archive collection system (internal or external).....	24
5.5.7	Procedures to obtain.....	24
5.6	Key changeover.....	24
5.7	Compromise and disaster recovery.....	24
5.8	CA or RA termination.....	25
<b>6</b>	<b>Technical Security Controls.....</b>	<b>26</b>
6.1	Key pair generation and installation.....	26
6.1.1	Key pair generation.....	26
6.1.2	Private key delivery to the subscriber.....	26
6.1.3	Public key delivery to certificate issuer.....	26
6.1.4	Public key delivery to relying parties.....	26
6.1.5	Key Sizes.....	26
6.1.6	Public key parameters generation and quality checking.....	26
6.1.7	Key usage (as per X.509 key usage field).....	26

<b>Last saved</b>	<b>Filename</b>	<b>Page</b>
27 September 2021	Cogito-PKIaaS-Resource-CP_v1.0.docx	8 of 70



## **X.509 Certificate Policy (CP)**

6.2	Private key production and cryptographic module engineering controls .....	26
6.2.1	Cryptographic module standards and controls .....	26
6.2.2	Private key (n of m) control .....	27
6.2.3	Private key escrow .....	27
6.2.4	Private key backup .....	27
6.2.5	Private key archive .....	27
6.2.6	Private key transfer into or from a cryptographic module .....	27
6.2.7	Private key storage on cryptographic module .....	27
6.2.8	Method of activating private key .....	27
6.2.9	Method of deactivating private key .....	27
6.2.10	Method of destroying private keys .....	27
6.2.11	Cryptographic module rating .....	27
6.3	Other aspects of key pair management .....	27
6.3.1	Public key archival .....	27
6.3.2	Certificate operational periods and key pair usage periods .....	27
6.4	Activation Data .....	28
6.4.1	Activation data generation and installation .....	28
6.4.2	Activation data protection .....	28
6.4.3	Other aspects of activation data .....	28
6.5	Computer security controls .....	28
6.6	Life cycle technical controls .....	28
6.7	Network security controls .....	28
6.8	Time stamping .....	28
<b>7</b>	<b>Certificate, CRL, and OCSP Profiles .....</b>	<b>29</b>
7.1	Certificate Profile .....	29
7.1.1	Version number(s) .....	29
7.1.2	Certificate extensions .....	29
7.1.3	Algorithm object identifiers .....	29
7.1.4	Name forms .....	29
7.1.5	Name constraints .....	29
7.1.6	Certificate policy object identifier .....	29
7.1.7	Usage of policy constraints extension .....	30
7.1.8	Policy qualifiers syntax and semantics .....	30
7.1.9	Processing semantics for the critical certificate policies extension .....	30

Last saved	Filename	Page
27 September 2021	Cogito-PKIaaS-Resource-CP_v1.0.docx	9 of 70

## **X.509 Certificate Policy (CP)**

7.2	CRL Profile .....	30
7.2.1	Version Number(s).....	30
7.2.2	CRL and CRL entry extensions .....	30
7.3	OCSP profile .....	30
7.3.1	Version number(s) .....	30
7.3.2	OCSP extensions.....	30
<b>8</b>	<b>Compliance Audit and Other Assessments .....</b>	<b>31</b>
8.1	Frequency or circumstances of assessment.....	31
8.2	Identity/qualifications of assessor .....	31
8.3	Assessor's relationship to assessed entity .....	31
8.4	Topics covered by assessment.....	31
8.5	Actions taken as a result of deficiency .....	31
8.6	Communication of results.....	31
<b>9</b>	<b>Other business and Legal Matters .....</b>	<b>32</b>
9.1	Fees .....	32
9.1.1	Certificate issuance or renewal fees.....	32
9.1.2	Certificate access fees.....	32
9.1.3	Revocation or status information access fees .....	32
9.1.4	Fees for other services .....	32
9.1.5	Refund policy .....	32
9.2	Financial responsibility .....	32
9.2.1	Insurance coverage .....	32
9.2.2	Other assets.....	32
9.2.3	Insurance or warranty coverage for end-entities .....	32
9.3	Confidentiality of business information .....	32
9.4	Privacy of personal information.....	32
9.5	Intellectual property rights.....	33
9.6	Representations and Warranties .....	33
9.7	Disclaimers of warranties .....	33
9.8	Limitations of liability .....	33
9.9	Indemnities .....	33
9.10	Term and termination .....	33
9.10.1	Term.....	33
9.10.2	Termination .....	33

<b>Last saved</b>	<b>Filename</b>	<b>Page</b>
27 September 2021	Cogito-PKIaaS-Resource-CP_v1.0.docx	10 of 70

## **X.509 Certificate Policy (CP)**

9.10.3	Effect of termination and survival.....	33
9.11	Individual Notices and communications with participants.....	33
9.12	Amendments .....	33
9.13	Dispute resolution provisions .....	33
9.14	Governing law .....	33
9.15	Compliance with applicable law .....	34
9.16	Miscellaneous provisions .....	34
9.17	Other provisions .....	34
A.1	Definitions.....	35
A.2	Acronyms.....	42
A.3	Interpretation .....	44
B.1	Secure Communications (RSA) .....	45
B.2	Secure Communications (ECC) .....	49
B.3	Secure Communications - Web Server (RSA).....	53
B.4	Secure Communications - Web Server (ECC).....	57
B.5	Secure Communications - Client Authentication (RSA).....	62
B.6	Secure Communications - Client Auth (ECC) .....	66

<b>Last saved</b>	<b>Filename</b>	<b>Page</b>
27 September 2021	Cogito-PKIaaS-Resource-CP_v1.0.docx	11 of 70

# 1 Introduction

Certificate policies are, in the X.509 version 3 digital certificate standard, the named set of rules regarding the applicability of a certificate to a particular community and/or class of applications with common security requirements. A CP may be used by a Relying Party to help in deciding whether a certificate, and the binding therein, are sufficiently trustworthy and otherwise appropriate for a particular application.

This Certificate Policy (CP) identifies the rules to manage the Cogito Group PKI as a Service (PKIaaS) Resource Certificates that are used to establish secure communication sessions using protocols, such as Transport Layer Security (TLS). It includes the obligations of the Public Key Infrastructure (PKI) entities, and how the parties, indicated below, use them. It does not describe how to implement these rules as that information is in the Cogito PKIaaS Certification Practice Statement (CPS), or documents referenced by the CPS. In general, the rules in this CP identify the minimum standards in terms of performance, security and/or quality.

The headings in this CP follow the framework set out in the Internet Engineering Task Force Request for Comment (RFC) 3647: Internet X.509 Public Key Infrastructure Certificate Policy and Certification Practices Framework.

A document hierarchy applies: the provisions of any applicable contract such as a Subscriber Agreement, Deed of Agreement or other relevant contract override the provisions of this CP. The provisions of this CP prevail over the provisions of CPS to the extent of any direct inconsistency. The provisions of CPS govern any matter on which this CP is silent. (Note: Where subtitled sections of the framework provide no additional information to detail provided in the CPS they have not been further extrapolated in this document).

This section identifies and introduces the set of provisions and indicates the types of entities and applications applicable for this CP.

## 1.1 Overview

This CP only applies to certificates issued to Cogito PKIaaS and Subscriber resources for the establishment of secure communication sessions using TLS or a related protocol and does not apply to other non-individuals (organisations, resources or devices) or any individuals.

No authority or privilege applies to a resource by becoming an approved Resource Certificate holder, other than confirming ownership by the Subscribing Agency or the Cogito PKIaaS.

## 1.2 Document Name and Identification

The title for this CP is Cogito PKI as a Service - Resource Certificates. The Object Identifier for this CP is: 1.2.36.151795998.4.1.1.3

**{iso (1) iso-member (2) australia (36) cogito-group-pty-ltd (151795998) Cogito PKIaaS(4) pki (1) certificate policy (1) Resource (3) }**

Extensions of this OID represent the certificate variants governed by this CP. They are identified in [Appendix B](#).

Last saved	Filename	Page
27 September 2021	Cogito-PKIaaS-Resource-CP_v1.0.docx	12 of 70

## **1.3 PKI Participants**

### **1.3.1 Certification Authorities**

The Certificate Authority(ies) (CA or CAs) that issue certificates under this CP are the Cogito PKIaaS CAs.

### **1.3.2 Registration Authorities**

The Registration Authority (RA), or RAs, that perform the registration functions under this CP are authorised by the Cogito Governance Risk and Compliance Group (GRCG). For those certificates issued in accordance with the Gatekeeper accreditation, a Gatekeeper accredited RA must be used. An RA is formally bound to perform the registration functions in accordance with this CP and other relevant Approved Documents.

### **1.3.3 Subscribers**

Resource certificates are only issued to non-person entities (NPE), not individuals.

In this document, and as allowed by the definition of a subscriber in the CPS, the subscriber of a Cogito PKIaaS resource certificate may, depending on the context, refer to the NPE whose name appears as the subject in the certificate, or to the person or legal entity that applied for that certificate.

In some instances, certain responsibilities of the Subscriber (person or legal entity) may be delegated to a Key Custodian. The Subscriber person or legal entity is fully responsible for the acts or omissions of its delegate.

### **1.3.4 Relying Parties**

See CPS for relying parties.

### **1.3.5 Other Participants**

See CPS for other participants and their responsibilities.

## **1.4 Certificate Usage**

### **1.4.1 Appropriate Certificate Uses**

Appropriate use for Certificates issued under this CP, in conjunction with their associated private key, is:

- i. To enable the Cogito PKIaaS or Subscribing agency resource to establish secure communication using TLS or a related protocol.

### **1.4.2 Prohibited Certificate Uses**

The prohibited uses for certificates issued under this CP are:

- i. Validating any resource to conduct any transaction or communication which is illegal, unauthorised, unethical, and/or unrelated to Cogito PKIaaS or Subscribing agency business.

<b>Last saved</b>	<b>Filename</b>	<b>Page</b>
27 September 2021	Cogito-PKIaaS-Resource-CP_v1.0.docx	13 of 70

## **X.509 Certificate Policy (CP)**

---

Engaging in a prohibited certificate use is a breach of the responsibilities and obligations agreed to by the Registration Officer (RO) and Cogito Group disclaims any and all liability in such circumstances.

### **1.5 Policy Administration**

#### **1.5.1 Organisation Administering the Document**

See CPS.

#### **1.5.2 Contact Person**

See CPS.

#### **1.5.3 Authority determining CPS suitability for the policy**

See CPS.

#### **1.5.4 CPS approval procedures**

See CPS.

### **1.6 Definitions, acronyms and interpretation**

Acronyms and terms used in this CP are defined in the CPS.

The Interpretation clause in Appendix C.3 of the CPS also applies to this CP.

<b>Last saved</b>	<b>Filename</b>	<b>Page</b>
27 September 2021	Cogito-PKIaaS-Resource-CP_v1.0.docx	14 of 70

## 2 Publication and Repository Responsibilities

### 2.1 Repositories

See CPS.

### 2.2 Publication of certification information

See CPS.

### 2.3 Time or Frequency of publication

See 4.9.7 for CRL issuance frequency. For further information, see CPS.

### 2.4 Access controls on repositories

See CPS.

Last saved	Filename	Page
27 September 2021	Cogito-PKIaaS-Resource-CP_v1.0.docx	15 of 70

### 3 Identification and Authentication

#### 3.1 Naming

##### 3.1.1 Types of Names

A clear distinguishable and unique Distinguished Name (DN) must be present in the certificate subject field.

##### 3.1.2 Need for Names to be Meaningful

The PKI Operator shall ensure that the DN in the subject field used to identify the Subject of a certificate is:

- i. Meaningful; and
- ii. Relates directly to an attribute or identifier of the resource.

##### 3.1.3 Anonymity or pseudonymity of Subscribers

Anonymous Certificates are not supported.

##### 3.1.4 Rules for interpreting various name forms

No stipulation as there is only one form.

##### 3.1.5 Uniqueness of Names

Names are unique within the Cogito PKIaaS name space.

##### 3.1.6 Recognition, authentication, and Role of Trademarks

See CPS.

#### 3.2 Initial identity validation

##### 3.2.1 Method to prove possession of private key

Certificate requests submitted to the CA must be PKCS#10 formatted requests where proof of possession of the Private Key is ensured and that the Key Pair is generated at the time the certificate request is created.

##### 3.2.2 Authentication of organisation entity

The RO is responsible for the resource being deployed. Authentication of organisation identity is therefore implicit in an RO's authorisation for registration of the resource with the PKI.

##### 3.2.3 Authentication of individual identity

This CP is for a non-human resource, and not an individual.

The identifying characteristics of the resource will be resource specific. The RO authenticates the identity of the resource during the approval of the certification request after checking that the information in the request is correct.

Last saved	Filename	Page
27 September 2021	Cogito-PKIaaS-Resource-CP_v1.0.docx	16 of 70



### **3.2.4 Non-Verified Subscriber information**

All Subscriber information included in the certificate request is verified by the RO.

### **3.2.5 Validation of authority**

Prior to the issue of a certificate, affiliation with the Cogito PKIaaS or subscriber organisation is validated by the RO

### **3.2.6 Criteria for interoperation**

See CPS.

## **3.3 Identification and authentication for re-key requests**

### **3.3.1 Identification and authentication for routine re-key**

No Stipulation.

### **3.3.2 Identification and authentication for re-key after revocation**

See Section 3.2.2 and Section 3.2.3

## **3.4 Identification and authentication for revocation requests**

Dual authentication is required for all requests to revoke (either two ROs or one RO and a PKI Operator). Prior to revocation, the request is verified, and the requestor and reasons documented.

Revocation requests, from sources other than a RO, should be digitally signed.

Revocation requests, from sources other than a RO, are authenticated by verifying that the request is signed by the person making the request, validating that the sender is affiliated with the Cogito PKIaaS or the subscribing agency, and checking that the request contains all the correct and required information.

Only in extraordinary (emergency) circumstances can a revocation request be submitted verbally.

See Section 4.9 for more information on revocation.

<b>Last saved</b>	<b>Filename</b>	<b>Page</b>
27 September 2021	Cogito-PKIaaS-Resource-CP_v1.0.docx	17 of 70

## 4 Certificate Lifecycle Operational Requirements

### 4.1 Certificate Application

#### 4.1.1 Who can submit a certificate application

Any individual who has an approved affiliation with the Cogito PKIaaS or a Subscribing Agency, and has a valid requirement, can submit an application for a certificate.

#### 4.1.2 Enrolment process and responsibilities

Using the resource's security functionality, the resource's administrator generates a key pair and submits a certificate request. The RO verifies the information in the request and then approves it for registration. The RA validates and signs the request, and sends it to the CA.

The resource's administrator is responsible for providing accurate information in an application for the correct certificate type. The RO is responsible for checking the accuracy of that information and verifying that the application is for a Subscribing agency resource prior to approval for registration.

### 4.2 Certificate application processing

#### 4.2.1 Performing identification and authentication functions

The RA signs and forwards the certificate request to the CA after receiving registration approval from an RO and validating the request. The CA only certifies certificate requests that are signed by an accredited Cogito PKIaaS RA.

#### 4.2.2 Approval or rejection of certificate applications

An RO may reject or approve a certificate application. Reasons for rejection may include invalid application, insufficient affiliation with the Cogito PKIaaS or subscriber organisation, or the provision of incorrect or insufficient identification details.

#### 4.2.3 Time to process certificate applications

See CPS.

### 4.3 Certificate Issuance

#### 4.3.1 CA actions during certificate issuance

See CPS.

#### 4.3.2 Notification to Subscriber by the CA of issuance of certificate

See CPS. In addition, the RO advises the resource's administrator when the certificate is available to be retrieved for installation.

### 4.4 Certificate Acceptance

#### 4.4.1 Conduct constituting certificate acceptance

Use of the certificate constitutes acceptance.

Last saved	Filename	Page
27 September 2021	Cogito-PKIaaS-Resource-CP_v1.0.docx	18 of 70

### 4.4.2 Publication of the certificate by the CA

See CPS.

### 4.4.3 Notification of certificate issuance by the CA to other entities

No stipulation.

## 4.5 Keypair and certificate usage

### 4.5.1 Subscriber private key and certificate usage

VA certificates are only issued to NPEs not individuals.

The Key Custodian must ensure that:

- The private key is protected from access by other parties in accordance with the KMP;
- The private key is only used in accordance with the key usage parameters set in the certificate; and
- The private key is no longer used following expiration or revocation of the certificate.

### 4.5.2 Relying Party public key and certificate usage

Section 1.4 and Section 1.3.4 detail the Relying Party's public key and certificate usage and responsibilities.

The interpretation and compliance with extended key usage attributes, and any associated limitations on the use of the certificate and/or private key, is in accordance with RFC 6818 and RFC 6960.

## 4.6 Certificate renewal

### 4.6.1 Circumstance for certificate renewal

See CPS for certificate renewal criteria.

Certificate renewal is only permitted in exceptional circumstances and must not be used to avoid certificate re-key or the associated identification and authentication process. For further information see CPS.

### 4.6.2 Who may request renewal

See CPS.

### 4.6.3 Processing certificate renewal requests

The process for certificate renewal requests is consistent with the processing of new certificate requests. As detailed in Section 4.2.1.

### 4.6.4 Notification of new certificate issuance to Subscriber

See Section 4.3.2.

Last saved	Filename	Page
27 September 2021	Cogito-PKIaaS-Resource-CP_v1.0.docx	19 of 70

## **X.509 Certificate Policy (CP)**

---

### **4.6.5 Conduct constituting acceptance of a renewal certificate**

See Section 4.4.1.

### **4.6.6 Publication of the renewal certificate by the CA**

See Section 4.4.2.

### **4.6.7 Notification of certificate issuance by the CA to other entities**

No stipulation.

## **4.7 Certificate Re-key**

### **4.7.1 Circumstance for certificate re-key**

See CPS.

### **4.7.2 Who may request certification of a new public key**

See Section 4.1.1.

### **4.7.3 Processing certificate re-keying requests**

Processing of certificate re-key requests is consistent with the processing of new certificate requests, as detailed in Section 4.2.1.

### **4.7.4 Notification of new certificate issuance to Subscriber**

See Section 4.3.2.

### **4.7.5 Conduct constituting acceptance of a re-keyed certificate**

See Section 4.4.1.

### **4.7.6 Publication of the re-keyed certificate by the CA**

See Section 4.4.2.

### **4.7.7 Notification of certificate issuance by the CA to other entities**

No Stipulation.

## **4.8 Certificate modification**

### **4.8.1 Circumstance for certificate modification**

The circumstances permitted for certificate modification include (but may not be limited to):

- i. Details in the certificate relevant to the certificate subject have changed or been found to be incorrect; and
- ii. Interoperation with approved "third party" PKI, or New Zealand Government assets and systems, require certificate attributes or contents inserted, modified or deleted.

The GRCC will determine other circumstances as appropriate.

<b>Last saved</b>	<b>Filename</b>	<b>Page</b>
27 September 2021	Cogito-PKIaaS-Resource-CP_v1.0.docx	20 of 70

See CPS for further information.

### 4.8.2 Who may request certificate modification

See Section 4.1.1.

### 4.8.3 Processing certificate modification requests

The process for certificate modification is consistent with Section 4.2. The identification and authentication procedures comply with Section 3.3.

### 4.8.4 Notification of new certificate issuance to Subscriber

See Section 4.3.2.

### 4.8.5 Conduct constituting acceptance of modified certificate

See Section 4.4.1.

### 4.8.6 Publication of the modified certificate by the CA

See CPS.

### 4.8.7 Notification of certificate issuance by the CA to other entities

No stipulation.

## 4.9 Certificate revocation and suspension

### 4.9.1 Circumstances for revocation

See CPS.

### 4.9.2 Who can request revocation

See CPS.

### 4.9.3 Procedure for revocation request

Revocation requests are verified on receipt in accordance with Section 3.4 and processed in priority order.

After verification the RO or PKIaaS Operator processes revocation requests, completing the revocation captures an auditable record of the process.

After a certificate is revoked, the CA includes the applicable certificate (serial number) in the CRL that is signed by the CA and published in the repositories.

### 4.9.4 Revocation request grace period

A grace period of one (1) business day is permitted.

The GRCG, or an approved delegate, in exceptional circumstances (such as security or law enforcement investigation), may approve a delay in submission of a revocation request. An audit record of this approval is required and must be submitted with the revocation request upon expiry of the approved delay.

Last saved	Filename	Page
27 September 2021	Cogito-PKIaaS-Resource-CP_v1.0.docx	21 of 70

## X.509 Certificate Policy (CP)

---

### 4.9.5 Time within which the CA must process the revocation request

A CA shall process revocation requests for certificates issued under this CP promptly after receipt.

### 4.9.6 Revocation checking requirement for relying parties

See CPS.

### 4.9.7 CRL issuance frequency (if applicable)

Refer to the Issuing CA's CP for the CRL issuance frequency.

### 4.9.8 Maximum latency for CRLs

Refer to the Issuing CA's CP.

### 4.9.9 Online revocation/status checking availability

Online Certificate Status Protocol service (OCSP) is available at:

<http://ocsp.<Subscriber>.securesme.com/>

Refer to the relevant Certificate Profile in [Appendix B](#) - if the certificate is issued with an OCSP access location reference (Authority Information Access extension), OCSP is available to the Relying Party as a certificate status checking method.

The latest CRL is available from the published repositories; refer to Section 2.1 and the certificates CRL Distribution Point (CDP) for further information.

### 4.9.10 On-line revocation checking requirements

No stipulation.

### 4.9.11 Other forms of revocation advertisements available

See CPS.

### 4.9.12 Special requirements re key compromise

No stipulation.

### 4.9.13 Circumstances for suspension

This CP does not support certificate suspension.

### 4.9.14 Who can request suspension

This CP does not support certificate suspension.

### 4.9.15 Procedure for suspension request

This CP does not support certificate suspension.

### 4.9.16 Limits on suspension period

This CP does not support certificate suspension.

Last saved	Filename	Page
27 September 2021	Cogito-PKIaaS-Resource-CP_v1.0.docx	22 of 70

## 4.10 Certificate status services

### 4.10.1 Operational Characteristics

See CPS.

### 4.10.2 Service Availability

See CPS.

### 4.10.3 Optional Features

No Stipulation.

## 4.11 End of subscription

See CPS.

## 4.12 Key escrow and recovery

Keys will not be escrowed.

Last saved	Filename	Page
27 September 2021	Cogito-PKIaaS-Resource-CP_v1.0.docx	23 of 70

## 5 FACILITY, MANAGEMENT, AND OPERATIONAL CONTROLS

### 5.1 Physical controls

See CPS.

### 5.2 Procedural Controls

See CPS.

### 5.3 Personnel controls

See CPS.

### 5.4 Audit logging procedures

See CPS.

### 5.5 Records archival

#### 5.5.1 Types of record archived

See CPS.

#### 5.5.2 Retention period for archive

See CPS.

#### 5.5.3 Protection of archive

See CPS.

#### 5.5.4 Archive backup procedures

See CPS.

#### 5.5.5 Requirements for timestamping of records

See CPS.

#### 5.5.6 Archive collection system (internal or external)

No Stipulation.

#### 5.5.7 Procedures to obtain

See CPS.

### 5.6 Key changeover

See CPS.

### 5.7 Compromise and disaster recovery

See CPS.

Last saved	Filename	Page
27 September 2021	Cogito-PKIaaS-Resource-CP_v1.0.docx	24 of 70



**5.8 CA or RA termination**

See CPS.

Last saved	Filename	Page
27 September 2021	Cogito-PKIaaS-Resource-CP_v1.0.docx	25 of 70

## 6 Technical Security Controls

### 6.1 Key pair generation and installation

#### 6.1.1 Key pair generation

Keys are primarily generated locally within the resource during the requesting process. Where a key pair is generated on behalf of the resource, the generation occurs centrally by a trusted role and following the placement of the keys in the custody of the resource the copy of the key pair is destroyed.

#### 6.1.2 Private key delivery to the subscriber

Generally, the key generation is performed within the resource, so no delivery is required. Where keys are generated externally the private key is delivered to the subscriber within a protected container known as a PKCS#12 file. The PKCS#12 format ensures the private key data is encrypted and is only accessible with the provision of an unlocking password.

Where resources are working in a failover configuration, cloning of the key pair and certificate is permitted. It is the Resource administrator's responsibility to ensure that they are installed in the correct location(s).

#### 6.1.3 Public key delivery to certificate issuer

Where keys are generated within the Resource, its public key is provided to the CA in a PKCS#10 certificate request file signed with the corresponding private key.

#### 6.1.4 Public key delivery to relying parties

See CPS.

#### 6.1.5 Key Sizes

The key sizes for RSA CAs a minimum of 2048 bits.

The key sizes for ECC CAs is a minimum of 384 bits.

#### 6.1.6 Public key parameters generation and quality checking

See CPS.

#### 6.1.7 Key usage (as per X.509 key usage field)

Keys issued under this CP allow a Subscriber to establish secure communication sessions using TLS or a related protocol.

See **Error! Reference source not found.** and CPS for further information.

### 6.2 Private key production and cryptographic module engineering controls

#### 6.2.1 Cryptographic module standards and controls

See CPS.

Last saved	Filename	Page
27 September 2021	Cogito-PKIaaS-Resource-CP_v1.0.docx	26 of 70

**6.2.2 Private key (n of m) control**

See CPS.

**6.2.3 Private key escrow**

Escrow of Keys does not occur.

**6.2.4 Private key backup**

See CPS.

**6.2.5 Private key archive**

See CPS.

**6.2.6 Private key transfer into or from a cryptographic module**

See CPS.

**6.2.7 Private key storage on cryptographic module**

See CPS.

**6.2.8 Method of activating private key**

Activating private keys occurs by the Key Custodian authenticating to the cryptographic module. The session stays alive until deactivated (see Section 6.2.9)

**6.2.9 Method of deactivating private key**

Deactivation can be achieved via:

- Shut down or restart of the system; or
- Shut down of the service that operates the token.

**6.2.10 Method of destroying private keys**

See CPS.

**6.2.11 Cryptographic module rating**

See CPS.

**6.3 Other aspects of key pair management**

**6.3.1 Public key archival**

See CPS.

**6.3.2 Certificate operational periods and key pair usage periods**

The Subscriber certificate has a maximum validity period of 2 years to limit the key lifetime. For further information, see CPS.

Last saved	Filename	Page
27 September 2021	Cogito-PKIaaS-Resource-CP_v1.0.docx	27 of 70

## 6.4 Activation Data

### 6.4.1 Activation data generation and installation

No stipulation.

### 6.4.2 Activation data protection

See CPS.

### 6.4.3 Other aspects of activation data

No stipulation.

## 6.5 Computer security controls

See CPS.

## 6.6 Life cycle technical controls

See CPS.

## 6.7 Network security controls

See CPS.

## 6.8 Time stamping

See CPS.

Last saved	Filename	Page
27 September 2021	Cogito-PKIaaS-Resource-CP_v1.0.docx	28 of 70

## 7 Certificate, CRL, and OCSP Profiles

### 7.1 Certificate Profile

#### 7.1.1 Version number(s)

All certificates are X.509 Version 3 certificates.

#### 7.1.2 Certificate extensions

See [Appendix B](#).

#### 7.1.3 Algorithm object identifiers

Certificates under this CP will use one of the following OIDs for signatures.

sha256WithRSAEncryption	{iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs-1(1) 11}
ecdsa-with-SHA384	{iso(1) member-body(2) us(840) ansi-X9-62(10045) signatures(4) ecdsa-with-SHA2(3) 3 }

**Table 1: Signature OIDs**

Certificates under this CP will use one of the following OIDs for identifying the algorithm for which the subject key was generated.

rsaEncryption	{iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs-1(1) 1}
Id-ecPublicKey	{iso(1) member-body(2) us(840) ansi-x9-62(10045) public-key-type (2) 1}
id-ecDH	{iso(1) identified-organization(3) certicom(132) schemes(1) ecdh(12) }
dhpublicnumber	{iso(1) member-body(2) us(840) ansi-x942(10046) number-type(2) 1}
Id-keyExchangeAlgorithm	{joint-iso-ccitt(2) country(16) us(840) organization(1) gov(101) dod(2) infosec(1) algorithms(1) 22}

**Table 2: Algorithm OIDs**

#### 7.1.4 Name forms

See CPS and [Appendix B](#) for further information.

#### 7.1.5 Name constraints

Name constraints are not present.

#### 7.1.6 Certificate policy object identifier

Certificates issued under this CP shall assert this CPs OID { 1.2.36.151795998.4.1.1.3 }

Certificates issued under this policy shall assert the following LoA OIDs for the LoA under which it was issued:

Resources:	Low	1.2.36.151795998.4.1.2.2.1
	Medium	1.2.36.151795998.4.1.2.2.2

Last saved	Filename	Page
27 September 2021	Cogito-PKIaaS-Resource-CP_v1.0.docx	29 of 70

## X.509 Certificate Policy (CP)

---

High

1.2.36.151795998.4.1.2.2.3

See also [Appendix B](#)

### 7.1.7 Usage of policy constraints extension

[See Appendix B.](#)

### 7.1.8 Policy qualifiers syntax and semantics

[See Appendix B.](#)

### 7.1.9 Processing semantics for the critical certificate policies extension

This CP does not require the certificate policies extension to be critical. Relying Parties whose client software does not process this extension do so at their own risk.

## 7.2 CRL Profile

### 7.2.1 Version Number(s)

CRLs issued shall be X.509 version 2 CRLs.

### 7.2.2 CRL and CRL entry extensions

See [Appendix B.](#)

## 7.3 OCSP profile

### 7.3.1 Version number(s)

OCSP is implemented using version 1 as specified under RFC 6960.

### 7.3.2 OCSP extensions

Refer to CPS and Validation Authority (VA) CP for full OCSP profile.

See [Appendix B](#) for full details.

Last saved	Filename	Page
27 September 2021	Cogito-PKIaaS-Resource-CP_v1.0.docx	30 of 70

## **8 Compliance Audit and Other Assessments**

### **8.1 Frequency or circumstances of assessment**

See CPS.

### **8.2 Identity/qualifications of assessor**

See CPS.

### **8.3 Assessor's relationship to assessed entity**

See CPS.

### **8.4 Topics covered by assessment**

See CPS.

### **8.5 Actions taken as a result of deficiency**

See CPS.

### **8.6 Communication of results**

See CPS.

<b>Last saved</b>	<b>Filename</b>	<b>Page</b>
27 September 2021	Cogito-PKIaaS-Resource-CP_v1.0.docx	31 of 70

## 9 Other business and Legal Matters

### 9.1 Fees

#### 9.1.1 Certificate issuance or renewal fees

The Cogito PKIaaS fees charged for certificates and related services can be obtained from <https://www.securesme.com/pricing/>.

#### 9.1.2 Certificate access fees

Certificates are published into the certificate directory, there is no additional fee for accessing certificates.

#### 9.1.3 Revocation or status information access fees

Revocation status is published in the CRL. There is no additional fee for accessing the CRL.

#### 9.1.4 Fees for other services

Fees for other Cogito PKIaaS services can be obtained from <https://www.securesme.com/pricing/>.

#### 9.1.5 Refund policy

Where a fee is charged for a certificate, once that certificate is issued a refund will not be provided except where Cogito is responsible for the error. Cogito may at its discretion issue a replacement certificate free of charge or refund the certificate.

### 9.2 Financial responsibility

#### 9.2.1 Insurance coverage

Cogito shall maintain a commercially reasonable level of insurance coverage for errors and omissions, either through an errors and omissions insurance program with an insurance carrier or a self insured retention.

#### 9.2.2 Other assets

No stipulation.

#### 9.2.3 Insurance or warranty coverage for end-entities

Cogito does not provide any insurance and/or extended warranty coverage for end entity certificates issued pursuant to the Gatekeeper framework.

### 9.3 Confidentially of business information

See CPS.

### 9.4 Privacy of personal information

See CPS.

Last saved	Filename	Page
27 September 2021	Cogito-PKIaaS-Resource-CP_v1.0.docx	32 of 70



## **9.5 Intellectual property rights**

See CPS.

## **9.6 Representations and Warranties**

See CPS.

## **9.7 Disclaimers of warranties**

See CPS.

## **9.8 Limitations of liability**

See CPS.

## **9.9 Indemnities**

See CPS.

## **9.10 Term and termination**

### **9.10.1 Term**

This CP and any amendments shall become effective upon publication in the repository and will remain in effect until notice of their termination is communicated by the Cogito PKIaaS on its repository or website.

The CP is available at <http://pki.gatekeepersecuresme.com/>

### **9.10.2 Termination**

See CPS.

### **9.10.3 Effect of termination and survival**

See CPS.

## **9.11 Individual Notices and communications with participants**

See CPS.

## **9.12 Amendments**

See CPS.

## **9.13 Dispute resolution provisions**

See CPS.

## **9.14 Governing law**

See CPS.

<b>Last saved</b>	<b>Filename</b>	<b>Page</b>
27 September 2021	Cogito-PKIaaS-Resource-CP_v1.0.docx	33 of 70

**9.15 Compliance with applicable law**

See CPS.

**9.16 Miscellaneous provisions**

See CPS.

**9.17 Other provisions**

See CPS.

<b>Last saved</b>	<b>Filename</b>	<b>Page</b>
27 September 2021	Cogito-PKIaaS-Resource-CP_v1.0.docx	34 of 70

## APPENDIX A. Definitions, Acronyms, and Interpretation

### A.1 Definitions

Accreditation Agencies	Those agencies that provide independent assurance that the facilities, practices, and procedures used to issue certificates comply with the relevant accreditation frameworks (policy, security and legal). Principally these will consist of the DTA.
Application (Request)	A formal request to be considered for a position or to be allowed to do or have something, submitted to an authority, institution, or organization.
Application (Software)	A computer application or relevant component of one (including any object, module, function, procedure, script, macro, or piece of code).
Approved Documents	The Approved Documents are those approved by the GRCG and include those approved by the Gatekeeper Competent Authority. E.g., CPS, CPs, ICTSP, SSP, KMP, DRBCP, IRP and PKI Operations Manual.
Authorised Key Retriever	An AKR is a RO who is authorised to retrieve confidentiality keys from the Key Archive Server (KAS).
Authorised RA	Has the meaning given to it in paragraph 1.3.2 of this CPS.
Business Day	Any day other than a Saturday, Sunday, or public holiday for the whole of the Australian Capital Territory. Traditionally such days are from 0900 to 1700.
Certificate	An electronic document signed by the Certification Authority which: <ul style="list-style-type: none"> <li>i. Identifies a Subscriber by way of a Subject Distinguished Name (Identity certificates) and a Resource by way of a Subject Distinguished Name and/or Subject Alternative Name (Resource certificates);</li> <li>ii. Binds the Subject to a Key Pair by specifying the Public Key of that Key Pair; and</li> <li>iii. Contains the information required by the Certificate Profile</li> </ul>
Certificate Assurance Level	See Level of Assurance.
Certificate Information	Information needed to generate a digital certificate required by the Certificate Profile.
Certificate Policy	Means the definition adopted by RFC3647, which defines a Certificate Policy as “A named set of rules that indicates the

Last saved	Filename	Page
27 September 2021	Cogito-PKIaaS-Resource-CP_v1.0.docx	35 of 70

## X.509 Certificate Policy (CP)

	applicability of a Certificate to a particular community and/or class of applications with common security requirements”.
Certificate Profile	A certificate profile provides details about the format and contents of a digital certificate, including, for a natural person, their Distinguished Name.
Certificate Repository	The Certificate Repository provides a scalable mechanism to store and distribute certificates, cross-certificates, and CRLs to end users of the PKI.
Certificate Revocation List	The published file which lists the Digital Certificates that have been revoked by the Issuing CA before their scheduled expiration.
Certificate Authority	A Certificate Authority (or Certification Authority) (CA) is an entity which issues digital certificates for use by other parties.
Certificate Store	Storage location for certificates on a computer or device.
Certification Practice Statement	<p>A statement of the practices that a Certification Authority employs in managing the Digital Certificates it issues (this includes the practices that a Registration Authority employs in conducting registration activities on behalf of that Certification Authority).</p> <p>These statements will describe the PKI certification framework, mechanisms supporting the application, insurance, acceptance, usage, suspension/revocation, and expiration of Digital Certificates signed by the CA, and the CA's legal obligations, limitations, and miscellaneous provisions.</p>
Common Name	Is the characteristic value within a Distinguished Name. Typically, it is a descriptive name of the user or service e.g., “Bruce Smith” or “Application Web Handler”. Where technically required, the Common Name can be the resources domain name.
Cross certification	The establishment of a trust relationship between two PKIs, where one CA signs another PKI's CA certificate. This creates a chain of trust allowing the subscribers of the cross-certifying CA to trust those of the cross-certified CA. If done two-ways (PKIs signing each other's CAs' certificates), mutual trust can be established.
Cross Certification Ceremony	The event where a cross-certification agreement is executed, i.e. one CA creates a cross-certification request to another CA. The cross-signing CA creates and returns the cross-certificate, signed with its own private key. The “ceremony” is a formal event and is witnessed by representatives of both CAs. Details of the event are recorded and signed by the witnesses to provide an audit record.
Custodian	A person who has custody of something, a keeper or guardian; in the context of PKI, usually a Key Custodian.

Last saved	Filename	Page
27 September 2021	Cogito-PKIaaS-Resource-CP_v1.0.docx	36 of 70

## X.509 Certificate Policy (CP)

Device	Device means any computer hardware or other electronic device.
Digital Signature	An electronic signature created using a Private Signing Key.
Directory Service	<p>A directory service is a software application - or a set of applications – that stores and organises information about a computer network's users and network resources, and that allows network administrators to manage users' access to the resources. Additionally, directory services act as an abstraction layer between users and shared resources.</p> <p>The X.500 and LDAP directory services are examples of general-purpose distributed hierarchical object-oriented directory technologies. Both offer complex searching and browsing capabilities are used for white pages, network information services, PKI, and a wide range of other applications.</p>
Distinguished Name (DN)	<p>A unique identifier assigned to, as relevant:</p> <ol style="list-style-type: none"> <li>i. The Subject identified by; and</li> <li>ii. The issuer of a Certificate, having the structure required by the Certificate Profile.</li> </ol>
Evaluated Product List (EPL)	<p>The Evaluated Product List is produced to assist in the selection of products that will provide an appropriate level of information security. The list, maintained by ASD, is published at:  <a href="https://www.cyber.gov.au/acsc/view-all-content/epl-products">https://www.cyber.gov.au/acsc/view-all-content/epl-products</a></p> <p>The EPL lists products that:</p> <ol style="list-style-type: none"> <li>i. Have completed Common Criteria (CC) or ITSEC certification;</li> <li>ii. Are in evaluation within the AISEP; or</li> <li>iii. Have completed some other recognised ASD evaluation methodology.</li> </ol>
Evaluation Assurance Level	<p>The Evaluation Assurance Level (EAL1 through EAL7) of a computer product or system is a numerical grade assigned following the completion of a Common Criteria security evaluation, an international standard in effect since 1999. The increasing assurance levels reflect added assurance requirements that must be met to achieve Common Criteria certification. The intent of the higher levels is to provide higher confidence that the system's principal security features are reliably implemented. See also Protection Profile.</p>
Evidence of identity	<p>Evidence (e.g. in the form of documents) issued to substantiate the identity of the presenting party, usually produced at the time of Registration (i.e. when authentication credentials are issued).</p>

Last saved	Filename	Page
27 September 2021	Cogito-PKIaaS-Resource-CP_v1.0.docx	37 of 70

## X.509 Certificate Policy (CP)

Exercised	To discharge or perform a function. An act of employing or putting into play.
Gatekeeper	The Commonwealth Government strategy to develop Public Key Infrastructure to facilitate Government online service delivery and electronic procurement.
Hard Token	A hard token, sometimes called an “authentication token”, is a hardware security device that is used to authorise a Subscriber. A common example of a hard token is a smartcard.
High Assurance Certificate (Gatekeeper)	A Digital Certificate issued by a Gatekeeper Accredited or Recognised Service Provider to Organisations and individuals for the purpose of transacting online with government agencies and whose risk and threat to data are assessed as high. This category is characterised by a requirement for a Formal Identity Verification Model EOI check by a Gatekeeper accredited Registration Authority.
Identity Certificate	An identity certificate is a certificate which uses a digital signature to bind together a public key with a human identity – information such as the name of a person, their address, and so forth. The certificate can be used to verify that a public key belongs to an individual.
Key	A Key is a string of characters used with a cryptographic algorithm to encrypt and decrypt.
Key Custodian	A key custodian refers to the authorised person appointed to manage a key on behalf of the subscriber.
Key Pair	A pair of asymmetric cryptographic Keys (e.g. one decrypts messages which have been encrypted using the other) consisting of a Public Key and a Private Key.
Level of Assurance	Levels of trust associated with a credential as measured by the associated technology, processes, and policy and practice statements controlling the operational environment. In the context of this CPS, the term refers to four levels of assurance of certificates (low, medium, high, very high) defined for the PKIaaS. A “No Assurance” level OID is used for test certificates.
Network Resource	Network Resources (devices) are units that mediate data in a computer network. Computer networking devices are also called network equipment and commonly include routers, gateways, switches, hubs, repeaters, and firewalls.
National Cryptographic Authority (NCA)	The NCA of Australia is the Australian Signals Directory (ASD). ASD also maintain a list of evaluated and approved security products for use by Australian Government agencies (Evaluated Products List – EPL).

Last saved	Filename	Page
27 September 2021	Cogito-PKIaaS-Resource-CP_v1.0.docx	38 of 70

## X.509 Certificate Policy (CP)

No Lone Zone	A physically secure area which has been defined as an area which when occupied must have 2 or more trusted personnel as occupants.
Non-Person Entity	An entity with a digital identity (for example an IP address or MAC address) that acts in cyberspace but is not a legal entity. This can include web sites, hardware devices, software applications, and information artefacts.
Modification (of Certificate)	Certificate modification means the issuance of a new certificate due to changes in the information in the certificate other than the Subscriber public key (RFC3647).
Object Identifier	An OID is a string of decimal numbers that uniquely identifies an object. These objects are typically an object class or an attribute. It serves to name almost every object type in X.509 Certificates, such as components of Distinguished Names and Certificate Policies
Online Certificate Status Protocol (OCSP)	Method of establishing the status of a certificate that has not expired. A PKI enabled client requests the status of a certificate from an OCSP responder. The responder provides a response (“good”, “revoked” or “unknown”) to the client. OCSP is a more bandwidth efficient method than the download of a full Certificate Revocation List (CRL).
Operational CA	A CA that issues and manages end-entity certificates.
Operator	Any individual who is assigned keys and certificates to perform functions within the PKI. They are not regarded as either Subscribers or Relying Parties for the purposes of the PKIaaS.
Personal Identity Verification (PIV)	Standard created by National Institute for Standards and Technology (NIST) in response to Homeland Security Presidential Directive 12 (HSPD 12) of Aug 2004. Full name “Personal Identity Verification of Federal Employees and Contractors”. Also known as FIPS 201. Specifies interfaces, biometrics, and algorithms for PIV compliant cards.
PKI Operations Manager	Manages PKI Operations of the PKIaaS.
PKI Operator	PKI Operators perform day to day operations, maintenance and support of the PKI systems managed as part of the PKIaaS.
PKI Software	Software programs that manage digital certificate lifecycle operations and token management.
PKI Systems Administrator	A PKI Systems Administrator performs system administration tasks on the PKIaaS systems.

Last saved	Filename	Page
27 September 2021	Cogito-PKIaaS-Resource-CP_v1.0.docx	39 of 70

## X.509 Certificate Policy (CP)

Private Certificate Signing Key	The Private Key used by the CA to digitally sign certificates.
Private Confidentiality Key	The key used by the addressee to decrypt messages, which have been encrypted using the corresponding Public Confidentiality Key.
Private Key	The private key in an asymmetric key pair that must be kept secret to ensure confidentiality, integrity authenticity, and non-repudiation.
Private Signing Key	A private key used to digitally sign messages on behalf of the relevant certificate Subject.
Protection Profile	<p>A document that stipulates the security functionality that must be included in Common Criteria evaluation to meet a range of defined threats.</p> <p>Protection Profiles also define the activities to be taken to assess the security function of an evaluated product.</p>
Public Key	The Key in an asymmetric key pair which may be made public.
Public Key Infrastructure (PKI)	The combination of hardware, software, people, policies, and procedures needed to create, manage, store, and distribute keys and certificates based on public key cryptography.
Public Key Technology (PKT)	Public Key Technology is the hardware and software used for encryption, signing and verification, as well as the software for managing Digital Certificates.
Registration Authority (RA)	<p>A Registration Authority (RA) is an entity that is responsible for one or more of the following functions on behalf of a CA:</p> <ol style="list-style-type: none"><li>i. Processing certificate application;</li><li>ii. Processing requests to revoke certificates; and</li><li>iii. Processing requests to renew, re-key or modify certificates.</li></ol> <p>Processing includes the identification and authentication of certificate applicants and approval or rejection of requests.</p> <p>See Section 1.3.2 (Registration Authorities) of this CPS and the relevant Certificate Policy (CP) for more information about the applicable RA.</p>
Registration Officer (RO)	A person authorised by a Registration Authority (RA) to perform RA functions in accordance with this CPS, the relevant Certificate Policy, and other applicable documentation.
Re-Key	A Subscriber or other participant generating a new keypair and applying for the issuance of a new certificate that certifies the new

Last saved	Filename	Page
27 September 2021	Cogito-PKIaaS-Resource-CP_v1.0.docx	40 of 70



## X.509 Certificate Policy (CP)

	public key. Normally used at the time of expiry of the certificate (RFC3647).
Relying Party	A recipient of a certificate who acts in reliance on that certificate and/or digital signatures verified using that certificate.
Renewal (of certificate)	Renewal means the issuance of a new certificate to the subscriber without changing the Subscriber's public key or any other information in the certificate (RFC3647). The validity period and serial number will be different in the renewed certificate.
Repository	A database of information (e.g. Certificate status, evaluated documents) which is made accessible to users including the Relying Parties.
Resource	Includes any Network Resource, Application, code, electronic service or process, Device, or data object that is capable of utilising a Certificate.
Resource Administrator	The Resource Administrator has the day-to-day responsibility for a resource and will in most cases be the person who requests, or installs, a certificate for the resource they are managing (also referred to as a Systems Administrator or Trusted Installer).
Resource Certificate	A Resource Certificate is a certificate issued in respect of a resource.
Revoke	To terminate a certificate prior to the end of its operational period.
Root CA	A CA that is the top of a certificate chain, i.e. its own certificate is self-signed.
Subordinate CA (SubCA)	A CA which has been established under the certificate path of a Root CA. A SubCA usually issues certificates to end entities and manages those certificates. See also Operational CA.
Subscriber	<p>A Subscriber is, as the context allows:</p> <ul style="list-style-type: none"> <li>i. For Identity Certificates, i.e. those issued to Person Entities (PE); the person whose Distinguished Name appears as the "Subject Distinguished Name" on the relevant Certificate; and</li> <li>ii. For Resource Certificates, i.e. those issued to Non-Person Entities (NPE); the person or legal entity that applied for that Certificate, and/or administers the system that utilises the Certificate.</li> </ul> <p>Individual CPs provide context for the definition of Subscriber relevant to that CP.</p>
Subscriber Agreement	An agreement between the relevant Service Provider and a Subscriber, which sets out the respective rights, obligations, and

Last saved	Filename	Page
27 September 2021	Cogito-PKIaaS-Resource-CP_v1.0.docx	41 of 70

## X.509 Certificate Policy (CP)

	liabilities of those parties, and which legally, binds those parties to the relevant Certificate Policy and Certification Practice Statement.
Superior CA	A CA which establishes/signs the certificate of a Subordinate CA.
Token	A hardware security device containing a user's Private Key(s) and Public Key Certificate.
Transport Layer Security (TLS)	A cryptographic protocol that provides security for communications over networks such as the Internet. TLS encrypts the segments of network connections at the Transport Layer end-to-end.
Universally Unique Identifier (UUID)	A universally unique identifier is a 128-bit label used for information in computer systems. The term globally unique identifier is also used, often in software created by Microsoft (GUID). When generated according to the standard methods, UUIDs are, for practical purposes, unique. See RFC 4122.
Validation Authority	<p>A Validation Authority (VA) is an entity that can perform one or more of the following functions:</p> <ol style="list-style-type: none"><li>i. Processing certificate status requests;</li><li>ii. Validating credentials and authentication requests;</li><li>iii. Validating signatures; and</li><li>iv. Other services related to PKI and online authentication.</li></ol> <p>The PKIaaS Validation Authority provides certificate status information through the provision of OCSP responders.</p>

Additional terms not defined in this Glossary, but which may be relevant can be found in the Identity and Access Management Glossary (refer to <https://www.dta.gov.au>). Where terms are defined in both the Identity and Access Management Glossary and this Glossary then for the purpose of Gatekeeper accreditation the definition in the Identity and Access Management Glossary will be determinative. The GRCG is the authoritative source of definitions relating to the Cogito PKIaaS, any requirement for clarification can be referred to the GRCG.

## A.2 Acronyms

ACT	Australian Capital Territory
AKR	Authorised Key Retriever
ASD	Australian Signals Directorate
CA	Certification Authority
CP	Certificate Policy

Last saved	Filename	Page
27 September 2021	Cogito-PKIaaS-Resource-CP_v1.0.docx	42 of 70

## X.509 Certificate Policy (CP)

---

CPS	Certification Practice Statement
CRL	Certificate Revocation List
DN	Distinguished Name
DRBCP	Disaster Recovery and Business Continuity Plan
DTA	Digital Transformation Agency
EAL	Evaluated Assurance Level
EOI	Evidence of Identity
EPL	Evaluated Products List
GRCG	Governance Risk and Compliance Group
HSM	Hardware Security Module
ICTSP	Information and Communication Technology Security Plan
IEC	International Electrotechnical Commission
IETF	Internet Engineering Taskforce
IP	Intellectual Property
IPR	Intellectual Property Rights
ISM	Australian Government Information Security Manual
ISO	International Standards Organisation
ITSEC	Information Technology Security Evaluation Criteria
KAS	Key Archive Server
KMP	Key Management Plan
LTSK	Long Term Key Storage
NCA	National Cryptographic Authority
OCSP	Online Certificate Status Protocol
OID	Object Identifier
PIN	Personal Identification Number
PKI	Public Key Infrastructure
PKT	Public Key Technology

Last saved	Filename	Page
27 September 2021	Cogito-PKIaaS-Resource-CP_v1.0.docx	43 of 70

## X.509 Certificate Policy (CP)

---

PSPF	Protective Security Policy Framework
RA	Registration Authority
RCA	Root Certification Authority
RFC	Request for Comment
RO	Registration Officer
SO	Security Officer
SRMP	Security Risk Management Plan
SSP	System Security Plan
URI	Uniform Resource Identifier
UTC	Coordinated Universal Time

### A.3 Interpretation

In Approved Documents, unless the contrary intention appears:

- i. A reference to the singular includes plural and vice versa;
- ii. Words importing a gender include any other gender;
- iii. A reference to a person includes a natural person, partnership, body corporate, association, governmental or local authority or agency, or Device or Application or other entity;
- iv. A reference to a document or instrument includes the document or instrument as altered, amended, supplemented or replaced from time to time;
- v. A reference to a section is a reference to the relevant section of that document;
- vi. An amendment or replacement of a document does not imply any consequent amendment or alteration to any other document;
- vii. Where a word or phrase is given a particular meaning, other parts of speech and grammatical forms of that word or phrase have corresponding meanings;
- viii. The meaning of general words is not limited by specific examples introduced by 'including', 'for example' or similar expressions;
- ix. The headings are for convenience only and are not to be used in the interpretation of an Approved Document; and
- x. Any appendix or attachment to an Approved Document (no matter how named) forms part of that document.

Last saved	Filename	Page
27 September 2021	Cogito-PKIaaS-Resource-CP_v1.0.docx	44 of 70

## APPENDIX B. Certificate and CRL Profiles and Formats

### B.1 Secure Communications (RSA)

Field	Critical	Value	Notes
Version		V3 (2)	Version 3 of X.509
Serial		<octet string>	Must be unique within the PKIaaS namespace
Issuer Signature Algorithm		SHA256WithRSAEncryption	
Issuer Distinguished Name		CN= <Subscriber>CA<Serial> OU= CAs OU= PKI O= <Subscriber> C= AU	Encoded as printable string. <Subscriber> is an identifier for the subscribing organisation <Serial> denotes the number after <Subscriber> that represents the issuing CA. starting at "001".
Validity Period		Not before <UTCtime> Not after <UTCtime>	Maximum 6 months from date of issue
Subject Distinguished Name		CN= <unique identifier> OU= Resources OU= PKI	<unique identifier> as determined by device. Note: This is an example only, actual distinguished names will describe the subscriber organisation

Last saved	Filename	Page
27 September 2021	Cogito-PKIaaS-Resource-CP_v1.0.docx	45 of 70

## X.509 Certificate Policy (CP)

---

Field	Critical	Value	Notes
		O= <Subscriber> C= AU	
Subject Public Key Information		Minimum 2048-bit RSA key modulus, rsaEncryption	
Issuer Unique Identifier		Not Present	
Subject Unique Identifier		Not Present	
Issuers Signature		SHA256WithRSAEncryption	
Authority Key Identifier	No	<octet string>	256 bit SHA256 hash of binary DER encoding of the issuing CA's public key.
Subject Key Identifier	No	<octet string>	256 bit SHA256 hash of binary DER encoding of subject's public key.
Key usage	Yes	digitalSignature keyEncipherment	
Extended key usage		serverAuth clientAuth	

Last saved	Filename	Page
27 September 2021	Cogito-PKlaaS-Resource-CP_v1.0.docx	46 of 70

## X.509 Certificate Policy (CP)

---

Field	Critical	Value	Notes
Private key usage period		Not Present	
Certificate policies	No	[1] Policy OID: { 1.2.36.151795998.4.1.1.3 } Policy Qualifier - CPS pointer: <a href="http://pki.gatekeeper.securesme.com/">http://pki.gatekeeper.securesme.com/</a>	The OID of this CP.
		[2] Policy OID: {1.2.36.151795998.4.1.2.2.2}	Level of Assurance – Medium (Resource). The Level of Assurance of this certificate.
		[3] Policy OID: {1.2.36.151795998.4.1.2.2.1}	Level of Assurance – Low (Resource). Included to allow the certificate to be used in lower assurance context.
Policy Mapping		Not Present	
Subject Alternative Name			IP Addresses URIs DNS Names
Issuer Alternative Name		Not Present	
Subject Directory Attributes		Not Present	

Last saved	Filename	Page
27 September 2021	Cogito-PKlaaS-Resource-CP_v1.0.docx	47 of 70

## X.509 Certificate Policy (CP)

Field	Critical	Value	Notes
Basic Constraints		Not Present	
Name Constraints		Not Present	
Policy Constraints		Not Present	
Authority Information Access	No	<p>[1] Access method: CAIssuer{1.3.6.1.5.5.7.48.2}</p> <p>Access location:  <a href="http://pki.&lt;Subscriber&gt;.securesme.com/Certificates/&lt;subscriber&gt;CA&lt;serial&gt;.cer">http://pki.&lt;Subscriber&gt;.securesme.com/Certificates/&lt;subscriber&gt;CA&lt;serial&gt;.cer</a></p> <p>[2] Access method: CAIssuer{1.3.6.1.5.5.7.48.2}</p> <p>Access location:  <a href="http://pki.&lt;Subscriber&gt;.securesme.com/Certificates/&lt;subscriber&gt;CA&lt;serial&gt;.p7b">http://pki.&lt;Subscriber&gt;.securesme.com/Certificates/&lt;subscriber&gt;CA&lt;serial&gt;.p7b</a></p> <p>[3] Access method: OCSP {1.3.6.1.5.5.7.48.1}</p> <p>Access location:  <a href="http://ocsp.&lt;Subscriber&gt;.securesme.com/">http://ocsp.&lt;Subscriber&gt;.securesme.com/</a></p>	
CRL Distribution Points	No	<p>[1] Distribution Point Name (http):  <a href="http://pki.&lt;Subscriber&gt;.securesme.com/crl/&lt;Subscriber&gt;CA&lt;Serial&gt;.crl">http://pki.&lt;Subscriber&gt;.securesme.com/crl/&lt;Subscriber&gt;CA&lt;Serial&gt;.crl</a></p>	<p>The CRL distribution point extension shall only populate the distributionPoint field. The field shall only contain the URI name form. The reasons and cRLIssuer fields shall not be populated. The CRL shall point to a full and complete CRL only (i.e. a CRL that does NOT contain the issuer distribution point extension).</p>

Last saved	Filename	Page
27 September 2021	Cogito-PKlaaS-Resource-CP_v1.0.docx	48 of 70



## X.509 Certificate Policy (CP)

Field	Critical	Value	Notes
		[2] Distribution Point Name (ldap): ldap://dir.<Subscriber>.securesme.com/cn=<subscriber>CA<serial>,ou=CAs,ou=PKI,o=<Subscriber>,c=AU?certificateRevocationList	

**Table 3: Secure Communications (RSA) Profile**

## B.2 Secure Communications (ECC)

Field	Critical	Value	Notes
Version		V3 (2)	Version 3 of X.509.
Serial		<octet string>	Must be unique within the PKIaaS namespace.
Issuer Signature Algorithm		ecdsa-with-SHA384	
Issuer Distinguished Name		CN= <Subscriber>CA<Serial> OU= CAs OU= PKI O= <Subscriber> C= AU	Encoded as printable string. <Subscriber> is an identifier for the subscribing organisation. <Serial> denotes the number after <Subscriber> that represents the issuing CA. starting at "001".

Last saved	Filename	Page
27 September 2021	Cogito-PKIaaS-Resource-CP_v1.0.docx	49 of 70

## X.509 Certificate Policy (CP)

---

Field	Critical	Value	Notes
Validity Period		Not before <UTCtime> Not after <UTCtime>	Maximum 6 months from date of issue.
Subject Distinguished Name		CN= <unique identifier> OU= Resources OU= PKI O= <Subscriber> C= AU	<unique identifier> as determined by device. Note: This is an example only, actual distinguished names will describe the subscriber organisation.
Subject Public Key Information		ecdsa-with-SHA384	
Issuer Unique Identifier		Not Present	
Subject Unique Identifier		Not Present	
Issuers Signature		SHA256WithRSAEncryption	
Authority Key Identifier	No	<octet string>	384 bit SHA384 hash of binary DER encoding of signing CA's public key.
Subject Key Identifier	No	<octet string>	384 bit SHA384 hash of binary DER encoding of subject's public key.

Last saved	Filename	Page
27 September 2021	Cogito-PKlaaS-Resource-CP_v1.0.docx	50 of 70

## X.509 Certificate Policy (CP)

---

Field	Critical	Value	Notes
Key usage	Yes	digitalSignature keyEncipherment	
Extended key usage		serverAuth clientAuth	
Private key usage period		Not Present	
Certificate policies	No	[1] Policy OID: { 1.2.36.151795998.4.1.1.3 } Policy Qualifier - CPS pointer: <a href="http://pki.gatekeeper.securesme.com/">http://pki.gatekeeper.securesme.com/</a>	The OID of this CP.
		[2] Policy OID: {1.2.36.151795998.4.1.2.2.2}	Level of Assurance – Medium (Resource). The Level of Assurance of this certificate.
		[3] Policy OID: {1.2.36.151795998.4.1.2.2.1}	Level of Assurance – Low (Resource). Included to allow the certificate to be used in lower assurance context.
Policy Mapping		Not Present	
Subject Alternative Name			IP Addresses URIs DNS Names

Last saved	Filename	Page
27 September 2021	Cogito-PKlaaS-Resource-CP_v1.0.docx	51 of 70

## X.509 Certificate Policy (CP)

---

Field	Critical	Value	Notes
Issuer Alternative Name		Not Present	
Subject Directory Attributes		Not Present	
Basic Constraints		Not Present	
Name Constraints		Not Present	
Policy Constraints		Not Present	
Authority Information Access	No	[1] Access method: CAIssuer{1.3.6.1.5.5.7.48.2} Access location: <a href="http://pki.&lt;Subscriber&gt;.securisme.com/Certificates/&lt;subscriber&gt;CA&lt;serial&gt;.cer">http://pki.&lt;Subscriber&gt;.securisme.com/Certificates/&lt;subscriber&gt;CA&lt;serial&gt;.cer</a> [2] Access method: CAIssuer{1.3.6.1.5.5.7.48.2} Access location: <a href="http://pki.&lt;Subscriber&gt;.securisme.com/Certificates/&lt;subscriber&gt;CA&lt;serial&gt;.p7b">http://pki.&lt;Subscriber&gt;.securisme.com/Certificates/&lt;subscriber&gt;CA&lt;serial&gt;.p7b</a> [3] Access method: OCSP {1.3.6.1.5.5.7.48.1} Access location: <a href="http://ocsp.&lt;Subscriber&gt;.securisme.com/">http://ocsp.&lt;Subscriber&gt;.securisme.com/</a>	

Last saved	Filename	Page
27 September 2021	Cogito-PKlaaS-Resource-CP_v1.0.docx	52 of 70

## X.509 Certificate Policy (CP)

Field	Critical	Value	Notes
CRL Distribution Points	No	[1] Distribution Point Name (http): http://pki.<Subscriber>.securesme.com/crl/<Subscriber>CA<Serial>.crl  [2] Distribution Point Name (ldap): ldap://dir.<Subscriber>.securesme.com/cn=<subscriber>CA<serial>,ou=CAs,ou=PKI,o=<Subscriber>,c=AU?certificateRevocationList	The CRL distribution point extension shall only populate the distributionPoint field. The field shall only contain the URI name form. The reasons and cRLIssuer fields shall not be populated. The CRL shall point to a full and complete CRL only (i.e. a CRL that does NOT contain the issuer distribution point extension).

Table 4: Secure Communications (ECC) Profile

### B.3 Secure Communications - Web Server (RSA)

Field	Critical	Value	Notes
Version		V3 (2)	Version 3 of X.509
Serial		<octet string>	Must be unique within the PKIaaS namespace.
Issuer Signature Algorithm		SHA256WithRSAEncryption	

Last saved	Filename	Page
27 September 2021	Cogito-PKIaaS-Resource-CP_v1.0.docx	53 of 70

## X.509 Certificate Policy (CP)

---

Field	Critical	Value	Notes
Issuer Distinguished Name		CN= <Subscriber>CA<Serial> OU= CAs OU= PKI O= <Subscriber> C= AU	Encoded as printable string. <Subscriber> is an identifier for the subscribing organisation. <Serial> denotes the number after <Subscriber> that represents the issuing CA. starting at "001".
Validity Period		Not before <UTCtime> Not after <UTCtime>	Maximum 6 months from date of issue.
Subject Distinguished Name		CN= <unique identifier> OU= Resources OU= PKI O= <Subscriber> C= AU	<unique identifier> as determined by device. Note: This is an example only, actual distinguished names will describe the subscriber organisation.
Subject Public Key Information		Minimum 2048-bit RSA key modulus, rsaEncryption	
Issuer Unique Identifier		Not Present	
Subject Unique Identifier		Not Present	

Last saved	Filename	Page
27 September 2021	Cogito-PKIaaS-Resource-CP_v1.0.docx	54 of 70

## X.509 Certificate Policy (CP)

Field	Critical	Value	Notes
Issuers Signature		SHA256WithRSAEncryption	
Authority Key Identifier	No	<octet string>	256 bit SHA256 hash of binary DER encoding of the issuing CA's public key.
Subject Key Identifier	No	<octet string>	256 bit SHA256 hash of binary DER encoding of subject's public key.
Key usage	Yes	DigitalSignature keyEncipherment dataEncipherment NonRepudiation	
Extended key usage		ServerAuthentication ClientAuthentication	
Private key usage period		Not Present	
Certificate policies	No	[1] Policy OID: { 1.2.36.151795998.4.1.1.3 } Policy Qualifier - CPS pointer: <a href="http://pki.gatekeeper.securesme.com/">http://pki.gatekeeper.securesme.com/</a>	The OID of this CP.
		[2] Policy OID: {1.2.36.151795998.4.1.2.2.2}	Level of Assurance – Medium (Resource). The Level of Assurance of this certificate.

Last saved	Filename	Page
27 September 2021	Cogito-PKlaaS-Resource-CP_v1.0.docx	55 of 70

## X.509 Certificate Policy (CP)

---

Field	Critical	Value	Notes
		[3] Policy OID: {1.2.36.151795998.4.1.2.2.1}	Level of Assurance – Low (Resource). Included to allow the certificate to be used in lower assurance context.
Policy Mapping		Not Present	
Subject Alternative Name			IP Addresses URIs DNS Names
Issuer Alternative Name		Not Present	
Subject Directory Attributes		Not Present	
Basic Constraints		Not Present	
Name Constraints		Not Present	
Policy Constraints		Not Present	
Authority Information Access	No	[1] Access method: CAIssuer{1.3.6.1.5.5.7.48.2} Access location: <a href="http://pki.&lt;Subscriber&gt;.securesme.com/Certificates/&lt;subscriber&gt;CA&lt;serial&gt;.cer">http://pki.&lt;Subscriber&gt;.securesme.com/Certificates/&lt;subscriber&gt;CA&lt;serial&gt;.cer</a>	

Last saved	Filename	Page
27 September 2021	Cogito-PKlaaS-Resource-CP_v1.0.docx	56 of 70



## X.509 Certificate Policy (CP)

Field	Critical	Value	Notes
		<p>[2] Access method: CAIssuer{1.3.6.1.5.5.7.48.2}</p> <p>Access location:  <a href="http://pki.&lt;Subscriber&gt;.securesme.com/Certificates/&lt;subscriber&gt;CA&lt;serial&gt;.p7b">http://pki.&lt;Subscriber&gt;.securesme.com/Certificates/&lt;subscriber&gt;CA&lt;serial&gt;.p7b</a></p> <p>[3] Access method: OCSP {1.3.6.1.5.5.7.48.1}</p> <p>Access location:  <a href="http://ocsp.&lt;Subscriber&gt;.securesme.com/">http://ocsp.&lt;Subscriber&gt;.securesme.com/</a></p>	
CRL Distribution Points	No	<p>[1] Distribution Point Name (http):  <a href="http://pki.&lt;subscriber&gt;.securesme.com/crl/&lt;Subscriber&gt;CA&lt;Serial&gt;.crl">http://pki.&lt;subscriber&gt;.securesme.com/crl/&lt;Subscriber&gt;CA&lt;Serial&gt;.crl</a></p> <p>[2] Distribution Point Name (ldap):  <a href="ldap://dir.&lt;Subscriber&gt;.securesme.com/cn=&lt;subscriber&gt;CA&lt;serial&gt;,ou=CAs,ou=PKI,o=&lt;Subscriber&gt;,c=AU?certificateRevocationList">ldap://dir.&lt;Subscriber&gt;.securesme.com/cn=&lt;subscriber&gt;CA&lt;serial&gt;,ou=CAs,ou=PKI,o=&lt;Subscriber&gt;,c=AU?certificateRevocationList</a></p>	The CRL distribution point extension shall only populate the distributionPoint field. The field shall only contain the URI name form. The reasons and cRLIssuer fields shall not be populated. The CRL shall point to a full and complete CRL only (i.e. a CRL that does NOT contain the issuer distribution point extension).

**Table 5: Secure Communications - Web Server (RSA) Profile**

## B.4 Secure Communications - Web Server (ECC)

Field	Critical	Value	Notes
Version		V3 (2)	Version 3 of X.509.

Last saved	Filename	Page
27 September 2021	Cogito-PKlaaS-Resource-CP_v1.0.docx	57 of 70

## X.509 Certificate Policy (CP)

---

Field	Critical	Value	Notes
Serial		<octet string>	Must be unique within the PKIaaS namespace.
Issuer Signature Algorithm		ecdsa-with-SHA384	
Issuer Distinguished Name		CN= <Subscriber>CA<Serial> OU= CAs OU= PKI O= <Subscriber> C= AU	Encoded as printable string. <Subscriber> is an identifier for the subscribing organisation. <Serial> denotes the number after <Subscriber> that represents the issuing CA. starting at "001".
Validity Period		Not before <UTCtime> Not after <UTCtime>	Maximum 6 months from date of issue.
Subject Distinguished Name		CN= <unique identifier> OU= Resources OU= PKI O= <Subscriber> C= AU	<unique identifier> as determined by device. Note: This is an example only, actual distinguished names will describe the subscriber organisation.
Subject Public Key Information		ecdsa-with-SHA384	

Last saved	Filename	Page
27 September 2021	Cogito-PKIaaS-Resource-CP_v1.0.docx	58 of 70

## X.509 Certificate Policy (CP)

---

Field	Critical	Value	Notes
Issuer Unique Identifier		Not Present	
Subject Unique Identifier		Not Present	
Issuers Signature		SHA256WithRSAEncryption	
Authority Key Identifier	No	<octet string>	384 bit SHA384 hash of binary DER encoding of signing CA's public key.
Subject Key Identifier	No	<octet string>	384 bit SHA384 hash of binary DER encoding of subject's public key.
Key usage	Yes	DigitalSignature keyEncipherment dataEncipherment NonRepudiation	
Extended key usage		ServerAuthentication ClientAuthentication	
Private key usage period		Not Present	
Certificate policies	No	[1] Policy OID: { 1.2.36.151795998.4.1.1.3 }	The OID of this CP.

Last saved	Filename	Page
27 September 2021	Cogito-PKlaaS-Resource-CP_v1.0.docx	59 of 70

## X.509 Certificate Policy (CP)

---

Field	Critical	Value	Notes
		Policy Qualifier - CPS pointer: <a href="http://pki.gatekeeper.securesme.com/">http://pki.gatekeeper.securesme.com/</a>	
		[2] Policy OID: {1.2.36.151795998.4.1.2.2.2}	Level of Assurance – Medium (Resource). The Level of Assurance of this certificate.
		[3] Policy OID: {1.2.36.151795998.4.1.2.2.1}	Level of Assurance – Low (Resource). Included to allow the certificate to be used in lower assurance context.
Policy Mapping		Not Present	
Subject Alternative Name			IP Addresses. URIs DNS Names
Issuer Alternative Name		Not Present	
Subject Directory Attributes		Not Present	
Basic Constraints		Not Present	
Name Constraints		Not Present	
Policy Constraints		Not Present	

Last saved	Filename	Page
27 September 2021	Cogito-PKlaaS-Resource-CP_v1.0.docx	60 of 70

## X.509 Certificate Policy (CP)

Field	Critical	Value	Notes
Authority Information Access	No	<p>[1] Access method: CAIssuer{1.3.6.1.5.5.7.48.2}</p> <p>Access location: http://pki.&lt;Subscriber&gt;.securisme.com/Certificates/&lt;subscriber&gt;CA&lt;serial&gt;.cer</p> <p>[2] Access method: CAIssuer{1.3.6.1.5.5.7.48.2}</p> <p>Access location: http://pki.&lt;Subscriber&gt;.securisme.com/Certificates/&lt;subscriber&gt;CA&lt;serial&gt;.p7b</p> <p>[3] Access method: OCSP {1.3.6.1.5.5.7.48.1}</p> <p>Access location: http://ocsp.&lt;Subscriber&gt;.securisme.com/</p>	
CRL Distribution Points	No	<p>[1] Distribution Point Name (http): http://pki.&lt;subscriber&gt;.securisme.com/crl/&lt;Subscriber&gt;CA&lt;Serial&gt;.crl</p> <p>[2] Distribution Point Name (ldap): ldap://dir.&lt;Subscriber&gt;.securisme.com/cn=&lt;subscriber&gt;CA&lt;serial&gt;,ou=CAs,ou=PKI,o=&lt;Subscriber&gt;,c=AU?certificateRevocationList</p>	The CRL distribution point extension shall only populate the distributionPoint field. The field shall only contain the URI name form. The reasons and cRLIssuer fields shall not be populated. The CRL shall point to a full and complete CRL only (i.e. a CRL that does NOT contain the issuer distribution point extension).

**Table 6: Secure Communications - Web Server (ECC) Profile**

Last saved	Filename	Page
27 September 2021	Cogito-PKlaaS-Resource-CP_v1.0.docx	61 of 70

## X.509 Certificate Policy (CP)

---

### B.5 Secure Communications - Client Authentication (RSA)

Field	Critical	Value	Notes
Version		V3 (2)	Version 3 of X.509.
Serial		<octet string>	Must be unique within the PKIaaS namespace.
Issuer Signature Algorithm		SHA256WithRSAEncryption	
Issuer Distinguished Name		CN= <Subscriber>CA<Serial> OU= CAs OU= PKI O= <Subscriber> C= AU	Encoded as printable string. <Subscriber> is an identifier for the subscribing organisation. <Serial> denotes the number after <Subscriber> that represents the issuing CA. starting at "001".
Validity Period		Not before <UTCtime> Not after <UTCtime>	Maximum 6 months from date of issue.
Subject Distinguished Name		CN= <unique identifier> OU= Resources OU= PKI O= <Subscriber> C= AU	<unique identifier> as determined by device. Note: This is an example only, actual distinguished names will describe the subscriber organisation.

Last saved	Filename	Page
27 September 2021	Cogito-PKIaaS-Resource-CP_v1.0.docx	62 of 70

## X.509 Certificate Policy (CP)

---

Field	Critical	Value	Notes
Subject Public Key Information		Minimum 2048-bit RSA key modulus, rsaEncryption	
Issuer Unique Identifier		Not Present	
Subject Unique Identifier		Not Present	
Issuers Signature		SHA256WithRSAEncryption	
Authority Key Identifier	No	<octet string>	256-bit SHA256 hash of binary DER encoding of the issuing CA's public key.
Subject Key Identifier	No	<octet string>	256-bit SHA256 hash of binary DER encoding of subject's public key.
Key usage	Yes	DigitalSignature keyEncipherment dataEncipherment NonRepudiation	
Extended key usage		ClientAuthentication	

Last saved	Filename	Page
27 September 2021	Cogito-PKIaaS-Resource-CP_v1.0.docx	63 of 70

## X.509 Certificate Policy (CP)

---

Field	Critical	Value	Notes
Private key usage period		Not Present	
Certificate policies	No	[1] Policy OID: { 1.2.36.151795998.4.1.1.3 } Policy Qualifier - CPS pointer: <a href="http://pki.gatekeeper.securesme.com/">http://pki.gatekeeper.securesme.com/</a>	The OID of this CP.
		[2] Policy OID: {1.2.36.151795998.4.1.2.2.2}	Level of Assurance – Medium (Resource). The Level of Assurance of this certificate.
		[3] Policy OID: {1.2.36.151795998.4.1.2.2.1}	Level of Assurance – Low (Resource). Included to allow the certificate to be used in lower assurance context.
Policy Mapping		Not Present	
Subject Alternative Name			IP Addresses URIs DNS Names
Issuer Alternative Name		Not Present	
Subject Directory Attributes		Not Present	

Last saved	Filename	Page
27 September 2021	Cogito-PKIaaS-Resource-CP_v1.0.docx	64 of 70



## X.509 Certificate Policy (CP)

Field	Critical	Value	Notes
Basic Constraints		Not Present	
Name Constraints		Not Present	
Policy Constraints		Not Present	
Authority Information Access	No	<p>[1] Access method: CAIssuer{1.3.6.1.5.5.7.48.2}</p> <p>Access location:  <a href="http://pki.&lt;Subscriber&gt;.securesme.com/Certificates/&lt;subscriber&gt;CA&lt;serial&gt;.cer">http://pki.&lt;Subscriber&gt;.securesme.com/Certificates/&lt;subscriber&gt;CA&lt;serial&gt;.cer</a></p> <p>[2] Access method: CAIssuer{1.3.6.1.5.5.7.48.2}</p> <p>Access location:  <a href="http://pki.&lt;Subscriber&gt;.securesme.com/Certificates/&lt;subscriber&gt;CA&lt;serial&gt;.p7b">http://pki.&lt;Subscriber&gt;.securesme.com/Certificates/&lt;subscriber&gt;CA&lt;serial&gt;.p7b</a></p> <p>[3] Access method: OCSP {1.3.6.1.5.5.7.48.1}</p> <p>Access location:  <a href="http://ocsp.gatekeeper.securesme.com/">http://ocsp.gatekeeper.securesme.com/</a></p>	
CRL Distribution Points	No	<p>[1] Distribution Point Name (http):  <a href="http://pki.&lt;Subscriber&gt;.securesme.com/crl/&lt;Subscriber&gt;CA&lt;Serial&gt;.crl">http://pki.&lt;Subscriber&gt;.securesme.com/crl/&lt;Subscriber&gt;CA&lt;Serial&gt;.crl</a></p>	<p>The CRL distribution point extension shall only populate the distributionPoint field. The field shall only contain the URI name form. The reasons and cRLIssuer fields shall not be populated. The CRL shall point to a full and complete CRL only (i.e. a CRL that does NOT contain the issuer distribution point extension).</p>

Last saved	Filename	Page
27 September 2021	Cogito-PKlaaS-Resource-CP_v1.0.docx	65 of 70

## X.509 Certificate Policy (CP)

Field	Critical	Value	Notes
		[2] Distribution Point Name (ldap): ldap://dir.<Subscriber>.securesme.com/cn=<subscriber>CA<serial>,ou=CAs,ou=PKI,o=<Subscriber>,c=AU?certificateRevocationList	

**Table 7: Secure Communications - Client Authentication (RSA) Profile**

## B.6 Secure Communications - Client Auth (ECC)

Field	Critical	Value	Notes
Version		V3 (2)	Version 3 of X.509.
Serial		<octet string>	Must be unique within the PKIaaS namespace.
Issuer Signature Algorithm		ecdsa-with-SHA384	
Issuer Distinguished Name		CN= <Subscriber>CA<Serial> OU= CAs OU= PKI O= <Subscriber> C= AU	Encoded as printable string. <Subscriber> is an identifier for the subscribing organisation. <Serial> denotes the number after <Subscriber> that represents the issuing CA. starting at "001".

Last saved	Filename	Page
27 September 2021	Cogito-PKIaaS-Resource-CP_v1.0.docx	66 of 70

## X.509 Certificate Policy (CP)

---

Field	Critical	Value	Notes
Validity Period		Not before <UTCtime> Not after <UTCtime>	Maximum 6 months from date of issue.
Subject Distinguished Name		CN= <unique identifier> OU= Resources OU= PKI O= <Subscriber> C= AU	<unique identifier> as determined by device. Note: This is an example only, actual distinguished names will describe the subscriber organisation.
Subject Public Key Information		ecdsa-with-SHA384	
Issuer Unique Identifier		Not Present	
Subject Unique Identifier		Not Present	
Issuers Signature		SHA256WithRSAEncryption	
Authority Key Identifier	No	<octet string>	384 bit SHA384 hash of binary DER encoding of signing CA's public key.
Subject Key Identifier	No	<octet string>	384 bit SHA384 hash of binary DER encoding of subject's public key.

Last saved	Filename	Page
27 September 2021	Cogito-PKlaaS-Resource-CP_v1.0.docx	67 of 70

## X.509 Certificate Policy (CP)

Field	Critical	Value	Notes
Key usage	Yes	DigitalSignature keyEncipherment dataEncipherment NonRepudiation	
Extended key usage		ClientAuthentication	
Private key usage period		Not Present	
Certificate policies	No	[1] Policy OID: { 1.2.36.151795998.4.1.1.3 } Policy Qualifier - CPS pointer: <a href="http://pki.gatekeeper.securesme.com/">http://pki.gatekeeper.securesme.com/</a>	The OID of this CP.
		[2] Policy OID: {1.2.36.151795998.4.1.2.2.2}	Level of Assurance – Medium (Resource). The Level of Assurance of this certificate.
		[3] Policy OID: {1.2.36.151795998.4.1.2.2.1}	Level of Assurance – Low (Resource). Included to allow the certificate to be used in lower assurance context.
Policy Mapping		Not Present	
Subject Alternative Name			IP Addresses

Last saved	Filename	Page
27 September 2021	Cogito-PKlaaS-Resource-CP_v1.0.docx	68 of 70

## X.509 Certificate Policy (CP)

Field	Critical	Value	Notes
			URIs DNS Names
Issuer Alternative Name		Not Present	
Subject Directory Attributes		Not Present	
Basic Constraints		Not Present	
Name Constraints		Not Present	
Policy Constraints		Not Present	
Authority Information Access	No	<p>[1] Access method: CAIssuer{1.3.6.1.5.5.7.48.2}</p> <p>Access location:  <a href="http://pki.&lt;Subscriber&gt;.securesme.com/Certificates/&lt;subscriber&gt;CA&lt;serial&gt;.cer">http://pki.&lt;Subscriber&gt;.securesme.com/Certificates/&lt;subscriber&gt;CA&lt;serial&gt;.cer</a></p> <p>[2] Access method: CAIssuer{1.3.6.1.5.5.7.48.2}</p> <p>Access location:  <a href="http://pki.&lt;Subscriber&gt;.securesme.com/Certificates/&lt;subscriber&gt;CA&lt;serial&gt;.p7b">http://pki.&lt;Subscriber&gt;.securesme.com/Certificates/&lt;subscriber&gt;CA&lt;serial&gt;.p7b</a></p> <p>[3] Access method: OCSP {1.3.6.1.5.5.7.48.1}</p>	

Last saved	Filename	Page
27 September 2021	Cogito-PKlaaS-Resource-CP_v1.0.docx	69 of 70

## X.509 Certificate Policy (CP)

---

Field	Critical	Value	Notes
		Access location: http://ocsp.<Subscriber>.securesme.com/	
CRL Distribution Points	No	[1] Distribution Point Name (http): http://pki.<Subscriber>.securesme.com/crl/<Subscriber>CA<Serial>.crl  [2] Distribution Point Name (ldap): ldap://dir.<Subscriber>.securesme.com/cn=<subscriber>CA<serial>,ou=CAs,ou=PKI,o=<Subscriber>,c=AU?certificateRevocationList	The CRL distribution point extension shall only populate the distributionPoint field. The field shall only contain the URI name form. The reasons and cRLIssuer fields shall not be populated. The CRL shall point to a full and complete CRL only (i.e. a CRL that does NOT contain the issuer distribution point extension).

**Table 8: Secure Communications - Client Authentication (ECC) Profile**

Last saved	Filename	Page
27 September 2021	Cogito-PKlaaS-Resource-CP_v1.0.docx	70 of 70